

MGL-FN-561/1~200mW



**LD PUMPED ALL-SOLID-STATE
YELLOW GREEN LASER
AT 561nm**

Yellow green laser at 561nm is made features of ultra compact, long lifetime, low cost and high stability, which is used in scientific experiment, optical sensor, measurement, instrument, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	561±1	
Operating mode	CW	
Output power (mW)	>1, 5, 10, 20, ... , 100	>100, ... , 200
Power stability (rms, over 4 hours)	<1%, <2%, <3%	<2%, <3%, <5%
Transverse mode	TEM ₀₀	
M ² factor	<1.2	
Beam diameter at the aperture (1/e ² , mm)	~2.0	
Beam divergence, full angle (mrad)	<1.5	
Polarization ratio	>100:1 Vertical ±5 degree (Horizontal Optional)	
Warm-up time (minutes)	<10	
Pointing stability after warm-up (mrad)	<0.05	
Beam height from base plate (mm)	27.4	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-LED PSU-H-FDA	
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option	
Expected lifetime (hours)	10000	
Warranty	1 year	



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MGL-FN-561	PSU-H-LED	PSU-H-FDA
<p>197(L)×70(W)×50(H) mm³, 2.0 kg</p>	<p>277 (L) ×145(W) ×106 (H) mm³, 2.6 kg</p>	<p>236(L) ×145(W) ×104(H) mm³, 2.3 kg</p>