

## MRL-S-671 /1~200mW



### LD PUMPED ALL-SOLID-STATE RED LASER

All solid state laser at 671nm is made features of ultra compact, small size, wide operating temperature, good sealing, long lifetime, cost -effectiveness and easy operating, working under the pressure of 0.02kPa, which is widely used in measurement, spectrum analysis, and laser lighting show, etc.



### SPECIFICATIONS

Model	MRL-S-671-A(Harsh condition)	MRL-S-671-B (Normal condition)		
Central wavelength (nm)	671±1			
Operating mode	CW			
Output power (mW)	>1, 5, 10, 20, ..., 100	>100, ..., 200		
Power stability (rms, over 4 hours)	<1%, <2%, <3%	<2%, <3%		
Transverse mode	TEM <sub>00</sub>			
M <sup>2</sup> factor	<1.2(<1.1 optional)	<1.2		
Beam diameter at the aperture( 1/e <sup>2</sup> ,mm)	0.7±0.05			
Beam divergence, full angle (mrad)	<1.5			
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)			
Pointing stability after warm-up (mrad)	<0.05			
Pointing stability Over Temp. (μrad/ °C)	<8			
Warm-up time (minutes)	<5			
Beam height from base plate (mm)	19			
Power Consumption(W)	<30			
Shock Tolerance(6ms)	7g laterally,15g vertically			
IP Rating	IP67	IP65		
Power supply(90-264VAC)	PSU-H-FDA	PSU-A-DP	PSU-A-FP	PSU-III-OEM-97 (5VDC)
Operating temperature (°C)	0-60	10-35		
Max. Heat Dissipation of Head(W)	10W@50°C	4W@25°C		
Modulation	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option			
Expected lifetime (hours)	10000			
Warranty	1 year			



MRL-S-671-B	PSU-A-D	PSU-A-F	PSU-III-OEM-97
 100 (L) x40 (W) x40(H) mm <sup>3</sup> , 0.36kg	 162 (L) x 144(W) x 70(H) mm <sup>3</sup> , 0.6kg	 162(L) x 144(W) x 55(H) mm <sup>3</sup> , 0.5kg	 94(L) X 75(W) X 49(H)mm <sup>3</sup> , 0.23kg