

PS-R-266/1~50mW

MODE-LOCKED PICOSECOND PULSED LASER AT 266nm

Mode-locked picosecond pulsed laser at 266nm is made features of short pulse duration, high repetition rate and good beam quality, which is used in laser medical treatment ,industrial processing,



SPECIFICATIONS

Wavelength (nm)	266±1	
Operating mode	Mode-locked	
Output power (mW)	@ Mode-locked mode	>1, 5, 10, ... , 50
Power stability (rms, over 4 hours)	<3%, <5%	
Transverse mode	TEM ₀₀	
Pulse duration(ps)	10~20	
Rep.rate(MHz)	48±1	
Beam divergence, full angle (mrad)	<4	
Beam diameter at the aperture (1/e ² ,mm)	~3	
Beam height from base plate (mm)	60	
Warm-up time (minutes)	<10	
Operating temperature (°C)	10~30	
Power Supply(90-264VAC)	PSU-Z-LED	
Expected lifetime (hours)	10000	
Warranty period	1 year	



PS-R-266	PSU-Z-LED	Water Chiller(WCH-600)
<p>545(L)×244(W)×9(H)mm³, 19kg</p>	<p>300(L)×300(W)×123(H)mm³, 6.2 kg</p>	<p>369(L)×350(W)×347(H) mm³, 22 kg</p>